





The WDT-3500 Walk-Around, Downdraft Bench Portable Cartridge Dust Collector by ProVent is the ideal ventilated and filtered work station for hand tool applications that need room to maneuver. Large pieces can be laid across the en-

tire body of the machine. Downdraft ventilated work areas are available on three sides of the unit.

Plus, the WDT-3500 uses 5" casters for complete portability. The machine can be positioned

Standard Features

- Integral High Efficiency Fan Assemblies

 AMCA Rated, Integral Direct Drive Fan
 Assemblies with Keyless Concentric Bushings
- Fibergrate Fiberglass Work Deck

 Exceptional strength-to-weight ratio. Nonconductive and slip resistant
- 12 Gauge Steel Construction

 Solid welded heavy steel for superior strength and longevity.
- Auto-Reverse Pulse Filter Cleaning
 Incorporated pressure gauge & time delay in
 NEMA 12 enclosure.
- NANO Fire Retardant Filters
 Provides >90% efficiency down to 1 micron
- Urethane Mastic Coating
 - Durethane DTM by PPG chemically resistant and extremely durable. Provides excellent corrosion resistance and has superior color and gloss retention.
- Excellent Airflow at the Deck -FPM at the deck averages 350
- Dust Removal Pan
 -Convenient single door entry to easily remove
 collected dust

HIGHLIGHTS

FULL-SIZE FILTERS

ProVent provides air-to-cloth ratios of 2:1 for true industrial filtration. Full-sized industrial filters provide higher consistent airflow and longer filter life. The performance of a ProVent down draft table is unmatched in the industry with 720 Sq Ft of total media.

PORTABLE

Heavy duty 5" industrial locking casters allow the WDT-3500 to be moved easily around the facility.

E. staff@proventilation.com Manufactured in Harbor Springs, Michigan P. 800-610-6010



Specifications

Motor HP	3HP
Integral Fan	High Efficiency, Backward Curved, Glass-Reinforced Polyamide Impeller
Voltage	460V/3PH
Filter Cleaning	Reverse Pulse 80-90 PSI Required
Number of Pulse Valves	2
Filters	MERV 15 - (4) Nano –Fire Retardant >90% down to 1 micron
Filter Racking	Horazontal
Housing Construction	12 Gauge Mild Steel Solid Welded
External Coating	Durethane DTM By PPG is a Direct-To-Metal Urethane Mastic Coating that is Chemically Resistant and Extremely Durable.
Work Deck	Fiberglass Work Surface 1 1/2 x 1 1/2 x 1 1/2 Grid
Work Deck Size	95" x 40"